

Not a Current Stock Product

Please contact our team for assistance.

- Pressure-sensitive adhesives
- Latex
- Latex
- Film

1.5 Mil Matte Clear Acetate Matte / AP151 Opaque @ 1.30 Cwt. / AP151 Heavy Coat Weight / 1.5 MIL CLEAR PET LINER L-3C / 1.5 MIL CLEAR PET LINER L-3 / L-10X

FACESTOCK		
A 1.5 mil matte clear film with excellent ink receptivity and printability.		
Type Film		
Tensile MD 20 Lbs/in	Tensile CD 25 Lbs/in	
Elong MD 325		
PROPERTIES		
Caliper	1.50 Mil	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
FSC No		
*Please contact your sales representative for details		

ADHESIVE		
An outstanding general purpose permanent opaque adhesive that has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting and stripping traits. Provides opacity for cover up applications.		
Type Permanent	Composition Latex	Shear 80
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 220 F
PROPERTIES	VALUE	
Stainless Steel	7.3 lbs/linear in.	

Glass	5,7 lbs/linear in.
Polyethylene	6,5
Corrugated	2.50 lbs./in.
Painted Metal	7.0 lbs/linear in.
Loop Tack	5.00 oz/in ²

REGULATORY APPROVAL		
RoHS Yes	Prop65 No	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food No
Indirect Food Yes		
*Please contact your sales representative for details		

ADHESIVE		
An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.		
Type Permanent	Composition Latex	
PROPERTIES	VALUE	
Glass	5.7 lbs/linear in.	
Polyethylene	6,5	
REGULATORY APPROVAL		
RoHS Yes	Prop65 No	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food No
Indirect Food Yes		
*Please contact your sales representative for details		

LINER		
A 1.5 Mil clear pet liner which is silicone coated one side to give a controlled release. Uniform caliper and high internal strength enhance the excellent die-cutting characteristics of this liner.		
Type 17617		
Tensile MD 32000	Tensile CD 0	
Tear MD 0	Tear CD 0	

DESCRIPTION	VALUE
Caliper	1.5
REGULATORY APPROVAL <div> <div>RoHS</div> <div>Yes</div> </div> <div> <div>TPCH</div> <div>Yes</div> </div> <div> <div>Direct Food</div> <div>No</div> </div> <div> <div>Prop65</div> <div>Yes</div> </div> <div> <div>CPSIA</div> <div>Yes</div> </div> <div> <div>REACH</div> <div>Yes</div> </div> <div> <div>UL</div> <div>No</div> </div>	
*Please contact your sales representative for details	

LINER A 1.5 mil polyester liner which has been silicone coated on two sides to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end usage, making it an outstanding liner for high speed, automatic applications.	
<div>Type</div> <div>19740</div> <div>Tensile MD</div> <div>32000</div> <div>Tear MD</div> <div>0</div> <div>Tensile CD</div> <div>0</div> <div>Tear CD</div> <div>0</div>	
DESCRIPTION	VALUE
Caliper	1.5
REGULATORY APPROVAL <div> <div>RoHS</div> <div>Yes</div> </div> <div> <div>TPCH</div> <div>Yes</div> </div> <div> <div>Direct Food</div> <div>No</div> </div> <div> <div>Prop65</div> <div>Yes</div> </div> <div> <div>CPSIA</div> <div>Yes</div> </div> <div> <div>REACH</div> <div>Yes</div> </div> <div> <div>UL</div> <div>No</div> </div>	
*Please contact your sales representative for details	

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com