

Not a Current Stock Product

Please contact our team for assistance.

- Pressure-sensitive adhesives
- Latex
- Film

1.5 Mil Matte Clear Acetate Matte / AP151 / LPG @ 1.30 Cwt. / 1.5 Mil Clear Polyester L-3

FACESTOCK

A 1.5 mil matte clear film with excellent ink receptivity and printability.

Type
Film

Tensile MD
20 Lbs/in

Tensile CD
25 Lbs/in

Elong MD
325

PROPERTIES

VALUE

Caliper

1.50 Mil

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

FSC
No

*Please contact your sales representative for details

ADHESIVE

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing & can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type
Permanent

Composition
Latex

Shear
80

Min. Application Temperature
35 F

Min. Service Temperature
-65 F

Max. Application Temperature
220 F

PROPERTIES

VALUE

Stainless Steel

7.3 lbs/linear in.

Glass

5,7 lbs/linear in.

Polyethylene

6.5

| | |
|----------------------|-------------------------|
| Corrugated | 2.50 lbs./in. |
| Painted Metal | 7.0 lbs/linear in. |
| Loop Tack | 5.00 oz/in ² |

REGULATORY APPROVAL

| | | |
|-----------------------------|---------------------|--------------------------|
| RoHS Yes | Prop65 No | REACH Yes |
| TPCH Yes | CPSIA Yes | Direct Food No |
| Indirect Food Yes | | |

*Please contact your sales representative for details

LINER

A 1.5 mil polyester liner which has been silicone coated one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end-usage, making it an outstanding liner for high speed, automatic applications.

| | |
|----------------------------|------------------------|
| Tensile MD 33000 | Tensile CD 0 |
| Tear MD 0 | Tear CD 0 |

| DESCRIPTION | VALUE |
|---------------------|-------|
| Basis Weight | 0 |
| Caliper | 1,5 |

REGULATORY APPROVAL

| | | |
|--------------------|----------------------|---------------------|
| RoHS Yes | Prop65 Yes | REACH Yes |
| TPCH Yes | CPSIA Yes | |

*Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
 Beontag
 6206 Wolf Creek Pike
 Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com