

Not a Current Stock Product

Please contact our team for assistance.

- Pressure-sensitive adhesives
- Acrylic
- Film

1.7 Mil Clear Acetate / ALL TEMP / 0.94 MIL PET

| | | |
|---|----------------------|---------------------|
| FACESTOCK A 1.7 mil clear film with excellent ink receptivity and printability. | | |
| Type Film | | |
| Tensile MD 12,500 psi | | |
| Tear MD 9 grams | | |
| | | |
| PROPERTIES | | VALUE |
| Caliper | | 1.7 mil |
| | | |
| REGULATORY APPROVAL | | |
| RoHS Yes | Prop65 Yes | REACH Yes |
| TPCH Yes | CPSIA Yes | UL No |
| FSC No | | |
| *Please contact your sales representative for details | | |

| | | |
|---|--|--|
| ADHESIVE An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Very good plasticizer, UV and solvent resistance. This adhesive offers a neutral ph level (Acid Free) | | |
| Type Permanent | Composition Acrylic | Shear 100 |
| Min. Application Temperature -20 F | Min. Service Temperature -65 F | Max. Application Temperature 160 F |
| | | |
| PROPERTIES | | VALUE |
| Stainless Steel | | 5.1 lbs/linear in. |
| Glass | | 4,4 lbs/linear in. |
| Polyethylene | | 4.2 |

| | | |
|---|-------------------------|---------------------------|
| Corrugated | 1.50 lbs./in. | |
| Painted Metal | 4.9 lbs/linear in. | |
| Loop Tack | 2.90 oz/in ² | |
| REGULATORY APPROVAL | | |
| RoHS Yes | Prop65 Yes | REACH Yes |
| TPCH Yes | CPSIA Yes | Direct Food Yes |
| Indirect Food Yes | | |
| *Please contact your sales representative for details | | |

| | | |
|--|----------------------|---------------------|
| LINER | | |
| An economical.94 mil clear polyester film liner good for an array of prime label applications. | | |
| Type colacril liner | | |
| DESCRIPTION | | |
| VALUE | | |
| Caliper | 0.94 mil | |
| REGULATORY APPROVAL | | |
| RoHS Yes | Prop65 Yes | REACH Yes |
| TPCH Yes | CPSIA Yes | UL No |
| Direct Food No | | |
| *Please contact your sales representative for details | | |

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
 Beontag
 6206 Wolf Creek Pike
 Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com