

Not a Current Stock Product

Please contact our team for assistance.

- Pressure-sensitive adhesives
- Acrylic
- Film

2.3 Mil Pearl White BOPP / AT333 / 1.2 MIL PET

FACESTOCK		
A coated one side BOPP face stock with excellent stability and cutting capabilities. This film has excellent stiffness, gloss, and opacity. Excellent whiteness and opacity.		
Type Film		
Tensile MD 7	Tensile CD 15	
Elong MD 160	Elong CD 30	
PROPERTIES		
Caliper	2.3	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	FSC No
*Please contact your sales representative for details		

ADHESIVE		
An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT333 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps.		
Type Permanent	Composition Acrylic	Shear 55
Min. Application Temperature -20 F	Min. Service Temperature -65 F	Max. Application Temperature 160 F
PROPERTIES		
VALUE		
Stainless Steel	4.5 lbs/linear in.	
Glass	1.3 lbs/linear in.	
Polyethylene	2.2	
Corrugated	1.35 lbs./in.	

Painted Metal	4.2 lbs/linear in.	
Loop Tack	2.15 oz/in ²	
REGULATORY APPROVAL		
RoHS Yes	Prop65 No	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food No
Indirect Food Yes		
*Please contact your sales representative for details		

LINER		
An economical 1.2 mil clear polyester film liner good for an array of prime label applications.		
Type 716666		
Tensile MD 30000	Tensile CD 0	
Tear MD 0	Tear CD 0	
DESCRIPTION		
Caliper	1.2	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No		
*Please contact your sales representative for details		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
 Beontag
 6206 Wolf Creek Pike
 Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com