Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives Acrylic

Paper

#4 Estate Label White Laid Finish / ALL TEMP / 40#SCK BASE LINER

FACESTOCK

Estate label is an uncoated face stock, wet strength grade, which meets the demanding packaging needs of the wine industry. The estate label combines prestige appearance with sophisticated production properties that ensure smooth performance on many high speed presses.

Type Paper				
PROPERTIES	VALUE			
Basis Weight	60			
Caliper	5.50 Mil			
Opacity	93			
Brightness	87			
REGULATORY APPROVAL				
RoHS Yes	Prop65 Yes	REACH Yes		
трсн Yes	CPSIA Yes	UL No		
FSC No				
*Please contact your sales representative for details				

ADHESIVE

An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Very good plasticizer, UV and solvent resistance. This adhesive offers a neutral ph level (Acid Free)

Type Permanent	Composition Acrylic	Shear 100
Min. Application Temperature -20 F	Min. Service Temperature -65 F	Max. Application Temperature 160 F
PROPERTIES	VALUE	
Stainless Steel	5.1 lbs/linear in.	

Polyethylene	4.2			
Corrugated	1.50 lbs./in.	1.50 lbs./in.		
Painted Metal	4.9 lbs/linear in.	4.9 lbs/linear in.		
Loop Tack	2.90 oz/in ²			
REGULATORY APPROVAL				
RoHS Yes	Prop65 Yes	REACH Yes		
TPCH	CPSIA	Direct Food		
Yes	Yes	Yes		
Indirect Food Yes				
*Please contact your sales representative for details				

LINER

Supercalendered Kraft (SCK liner). This paper has a smooth surface with a consistent caliper. Due to its high internal strength, it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре 18840				
Tensile MD	Tensile CD			
34	22			
Tear MD	Tear CD			
32	34			
DESCRIPTION	VALUE			
Basis Weight	40			
Caliper	2.5			
RoHS Yes	Prop65 Yes	REACH Yes		
трсн Yes	CPSIA Yes	UL No		
	162			
Direct Food No				
*Please contact your sales representative for details				

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

or for incidental or consequential damages. BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG's standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>