Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives Acrylic

Film

4 mil Soft White Vinyl / TR-1 / 4.6 Mil Layflat L-3

FACESTOCK

A 4 mil flexible white vinyl with polymeric plasticizers, formulated to provide optimum performance with pressure sensitive adhesives. The top-coating provides outstanding adhesion to various printing inks.

Туре Film			
Tensile MD	Tensile CD		
3900	3800		
Tear MD	Tear CD		
100	100		
PROPERTIES	VALUE		
Caliper	4.0		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	

*Please contact your sales representative for details

ADHESIVE

Adhesive(TR1 @ 1.10 Cwt.): A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.

Type Removable	Composition Acrylic	
PROPERTIES	VALUE	
Glass	0lbs/linear in.	
Polyethylene	0.8	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
трсн	CPSIA	Direct Food

Indirect Food Yes

*Please contact your sales representative for details

LINER

A clay coated kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand all diecutting, margin punching, perforating, fanfolding and refolding processes. It is an excellent layflat liner.

Туре 719363			
Tensile MD 51	Tensile CD O		
Tear MD 0	Tear CD 100		
DESCRIPTION	VALUE		
Basis Weight	72		
Caliper	4.6		
REGULATORY APPROVAL			
RoHS Yes	Prop65 Yes	REACH Yes	
трсн Yes	CPSIA Yes	UL No	
Direct Food No			
*Please contact your sales representa	tive for details		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>