

Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives

Acrylic

Film

4 White Direct Thermal BOPP / Ultra-Removable Adhesive

Facestock

Facestock (4.0 mil White DT BOPP): A white direct thermal top coated, biaxially oriented (BOPP) film that may be used in a wide variety of pressure sensitive label applications. The white polypropylene is treated one side with a print receptive coating for superb ink adhesion, and has great stiffness for efficient dispensability.

Type

Film

Tensile MD

7,000

Tensile CD

19,000 lbs/i

Elong MD

220

Elong CD

38

Properties

Value

Caliper

4.0 mil

Regulatory Approval

RoHS

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

UL

No

FSC

No

*Please contact your sales representative for details

Adhesive

An ultra-removable emulsion acrylic adhesive with low tack on smooth flat surfaces that can be cleanly removed after extended periods of time. This adhesive is suitable for glass, counter tops, painted metal, smooth painted walls, and stainless steel. This adhesive should be qualified for end-use suitability.

Type

Removable

Composition

Acrylic

Min. Application Temperature

40 F

Min. Service Temperature

-10 F

Max. Application Temperature

150 F

Properties	Value
Stainless Steel	0.2 lbs/linear in.
Glass	0.3
Polyethylene	0.0
Corrugated	0.01 lbs./in.
Painted Metal	0.2 lbs/linear in.
Loop Tack	0

Regulatory Approval

RoHS Yes	Prop65 No	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No	Indirect Food Yes	FDA 21 CFR 175.105, BfR XIV No

*Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages. BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
 Beontag
 6206 Wolf Creek Pike
 Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com