

Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives Latex

55# Semigloss / AP151@ 2.30 Cwt. / 1.5 MIL CLEAR PET LINER L-3

FACESTOCK

A calendar coated one side semigloss stock with excellent ink receptivity and print characteristics. This stock offers an 88% brightness and opacity and a 70% gloss rating.

Туре

Paper

Tensile CD

16 lb/in

Tear MD

51 g

PROPERTIES	VALUE
------------	-------

Basis Weight 55 lb/3300sf

Caliper 2.9 mil

REGULATORY APPROVAL

RoHS Prop65 **REACH** Yes Yes Yes **CPSIA TPCH** UL No Yes Yes

FSC No

ADHESIVE

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type Permanent	Composition Latex
PROPERTIES	VALUE
Glass Polyethylene	5,7 lbs/linear in. 6.5

^{*}Please contact your sales representative for details

REGULATORY APPROVAL

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes

Indirect Food

Yes

*Please contact your sales representative for details

LINER

A 1.5 mil polyester liner which has been silicone coated one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end-usage, making it an outstanding liner for high speed, automatic applications.

No

Type 619827

Tensile MD Tensile CD

32000

 Tear MD
 Tear CD

 0
 0

DESCRIPTION VALUE

Caliper 1.5

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

Direct Food

No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com

^{*}Please contact your sales representative for details