

Not a Current Stock Product

Please contact our team for assistance.

- Pressure-sensitive adhesives
- Acrylic
- Paper

60# Semigloss / TS700A @ 1.10 Cwt. / 40#SCK L-3

FACESTOCK A coated one side semigloss stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 88% Brightness and an 90% opacity.		
Type Paper		
Tensile MD 17 lbs/in		
Tear CD 56 g		
PROPERTIES		
VALUE		
Basis Weight		
60		
Caliper		
3.1		
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
FSC No		
*Please contact your sales representative for details		

ADHESIVE A synthetic acrylic adhesive that has good long term removability from a wide variety of plastic surfaces. It also displays excellent die-cutting and stripping characteristics.		
Type Removable	Composition Acrylic	Shear 0
Min. Application Temperature 40 F	Min. Service Temperature -65 F	Max. Application Temperature 200 F
PROPERTIES		
VALUE		
Glass		
0lbs/linear in.		
Polyethylene		
6,5lbs/linear in.		

Painted Metal			1.5 lbs/linear in.
REGULATORY APPROVAL			
RoHS Yes	Prop65 Yes	REACH Yes	
TPCH Yes	CPSIA Yes	Direct Food No	
Indirect Food Yes			
*Please contact your sales representative for details			

LINER			
Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.			
Type 5517342			
Tensile MD 34	Tensile CD 22		
Tear MD 32	Tear CD 34		
DESCRIPTION	VALUE		
Basis Weight	40		
Caliper	2.5		
REGULATORY APPROVAL			
RoHS Yes	Prop65 Yes	REACH Yes	
TPCH Yes	CPSIA Yes	UL No	
Direct Food No			
*Please contact your sales representative for details			

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
 Beontag
 6206 Wolf Creek Pike
 Trotwood, OH 45426
 800-358-4448
orders.us@beontag.com