

Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives Latex Paper

7 mil C1S TT Tag / TL250 / LPG @ 2.50 Cwt.

FACESTOCK		
Type Paper		
Tensile MD 60 Lbs/in	Tensile CD 32 Lbs/in	
Tear MD 150 Grams	Tear CD 160 Grams	
PROPERTIES	VALUE	
Basis Weight	119lbs/3300 sq ft	
Caliper	6.90 Mil	
Brightness	88	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	FSC No
*Please contact your sales representative for details		

ADHESIVE		
An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used fo r tire label and many other difficult to label substrates.		
Type Permanent	Composition Latex	Shear 80
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 220 F
PROPERTIES	VALUE	
Stainless Steel	8.3 lbs/linear in.	
Glass	6,7lbs/linear in.	
Polyethylene	7,5	
Corrugated	2.90 lbs./in.	
Painted Metal		

8.0 lbs/linear in.

Loop Tack

5.40 oz/in²

REGULATORY APPROVAL

RoHS
Yes

Prop65
No

REACH
Yes

TPCH
Yes

CPSIA
Yes

Direct Food
No

Indirect Food
Yes

*Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com