## Not a Current Stock Product

Latex

Please contact our team for assistance.

Pressure-sensitive adhesives

## AP151

## ADHESIVE

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

<b>Composition</b> Latex	<b>Shear</b> 80
<b>Min. Service Temperature</b> -65 F	<b>Max. Application Temperature</b> 220 F
VALUE	
7.3 lbs/linear in.	
5.7 lbs/linear in.	
6.5	
2.50 lbs./in.	
7.0 lbs/linear in.	
5.00 oz/in <sup>2</sup>	
Prop65 No	<b>REACH</b> Yes
CPSIA	Direct Food
Yes	Yes
	Latex Min. Service Temperature -65 F VALUE 7.3 lbs/linear in. 5.7 lbs/linear in. 6.5 2.50 lbs./in. 7.0 lbs/linear in. 5.00 oz/in <sup>2</sup> Prop65 No CPSIA Yes

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG's standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>