

Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives Hotmelt Ru

Cast Coated / SSP 50N

FACESTOCK

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

Type Paper

Tensile CD Tensile MD 25 Lbs/in 0 Lbs/in **Tear MD Tear CD** 35 Grams 40 Grams

PROPERTIES VALUE

Basis Weight 57 # Rm 24 x 26

3.70 Mil Caliper

REGULATORY APPROVAL

REACH RoHS Prop65 Yes Yes Yes **TPCH CPSIA** UL Yes Yes No

FSC No

ADHESIVE

General purpose, strong permanent adhesive with good chill characteristics. ScandStick Permanent 50N has excellent initial tack with high bond strength at elevated, room and chilled temperatures, as well as in moist conditions. It has been formulated to adhere to a wide variety of substrates, including corrugated cardboard, low surface energy materials like polyethylene and non-polar surfaces. SSP 50N provides enhanced conversion characteristics, allowing die-cutting at higher speeds and is designed for both paper and synthetic face materials. Limitation: Not suitable for labelling plasticized

Type Perm	Composition Hotmelt Ru
PROPERTIES	VALUE
Glass	Olbs/linear in.
Polyethylene	0

^{*}Please contact your sales representative for details

REGULATORY APPROVAL

Prop65 REACH **RoHS** Yes Yes Yes

TPCH CPSIA UL Yes Yes No

Direct Food Indirect Food FDA 21 CFR 175.105, BfR XIV

No Yes No

*Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com