

Pressure-sensitive adhesives

Acrylic

Paper

# 100# UNCOATED TAG / TR440 @ 1.0 Cwt. / 3.4 MIL LAYFLAT L-5

## ITEM #92377

$\Gamma\Lambda$	CE	CT	$\sim$	^	1
ГΑ	LΕ	OΙ	u	u	N

An uncoated tag stock that has a smooth consistent surface for ease in printing.

**Type** Paper

**Tear MD**135 Grams
150 Grams

PROPERTIES VALUE

**Basis Weight** 100 # Rm 25 x 38

Caliper 7.50 Mil

Brightness 84

#### **REGULATORY APPROVAL**

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 Yes
 No

# **ADHESIVE**

A specialty clear acrylic adhesive showing good initial removable tack with high shear and high removable adhesion. This adhesive has excellent clarity & minimum cold flow. Good removability on a wide range of substrates including corrugated and many plastic surfaces.

TypeCompositionShearRemovableAcrylic110

Min. Application Temperature Min. Service Temperature Max. Application Temperature

40 F -65 F 150 F

PROPERTIES VALUE

**Stainless Steel** 4.7 lbs/linear in.

**Glass** 3lbs/linear in.

Polyethylene 1.4

Corrugated 1.20 lbs./in.

Painted Metal 4.2 lbs/linear in.

**Loop Tack** 1.70 oz/in<sup>2</sup>

<sup>\*</sup>Please contact your sales representative for details

#### **REGULATORY APPROVAL**

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes No

#### **Indirect Food**

Yes

## **LINER**

A bleached kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand die-cutting, marginal punching, perforating, fanfolding and refolding process while providing excellent dimensional stability.

Tensile MD Tensile CD

35 15

 Tear MD
 Tear CD

 50
 75

**DESCRIPTION** VALUE

Basis Weight 0

Caliper 3,4

# **REGULATORY APPROVAL**

RoHSProp65REACHYesYesYes

TPCH CPSIA
Yes Yes

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details

<sup>\*</sup>Please contact your sales representative for details