

Pressure-sensitive adhesives

Acrylic

Paper

# 12 PT C1S TAG / AT333 @ 1.30 Cwt. / 40#SCK L-3

#### ITEM #87583

#### **FACESTOCK**

A premium coated one side stock with outstanding ink receptivity and print characteristics. This tag offers a 90 brightness, full double clay coating one side, high stiffness, excellent smoothness and gloss.

### Type

Paper

PROPERTIES	VALUE

**Basis Weight** 123 # Rm 24 x 26

Caliper 12.00 Mil

Brightness 90

#### **REGULATORY APPROVAL**

RoHS	Prop65	<b>REACH</b>
Yes	Yes	Yes
TPCH	<b>CPSIA</b>	<b>FSC</b>
Yes	Yes	No

<sup>\*</sup>Please contact your sales representative for details

## **ADHESIVE**

An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT333 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps.

<b>Type</b> Permanent	<b>Composition</b> Acrylic	<b>Shear</b> 60
Min. Application Temperature -20 F	<b>Min. Service Temperature</b> -65 F	<b>Max. Application Temperature</b> 160 F
PROPERTIES	VALUE	
Stainless Steel	4.7 lbs/linear in.	
Glass	1,3lbs/linear in.	
Polyethylene	2.2	
Corrugated	1.40 lbs./in.	
Painted Metal	4.4 lbs/linear in.	
Loop Tack	2.20 oz/in <sup>2</sup>	

**REACH RoHS** Prop65 No Yes Yes **TPCH CPSIA Direct Food** Yes Yes No

**Indirect Food** 

Yes

#### **LINER**

A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.

Type 5517342

**Tensile MD Tensile CD** 30 Lbs/In 20 Lbs/In Tear MD Tear CD 34 Grams 32 Grams

**DESCRIPTION VALUE** 

**Basis Weight** 40.5 Lbs/Rm

Caliper 2.5 Mil

#### **REGULATORY APPROVAL**

REACH Prop65 **RoHS** Yes Yes Yes **TPCH CPSIA** UL No Yes Yes

**Direct Food** 

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details

<sup>\*</sup>Please contact your sales representative for details