

Pressure-sensitive adhesives

Acrylic

Paper

# 12" X 18" BRIGHT WHITE GLOSS / PERMANENT / 80# SCOREBACK L-3

ITEM #SC-204

## **FACESTOCK**

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity.

**Type**Paper

Tensile MD
35 Lbs/in
19 Lbs/in
Tear MD
Tear CD
47 Grams
46 Grams

 PROPERTIES
 VALUE

 Basis Weight
 60 # Rm 25 x 38

 Caliper
 3.20 Mil

 Opacity
 88

 Brightness
 90

## **REGULATORY APPROVAL**

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 No
 No

#### **ADHESIVE**

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

<b>Type</b> Permanent	Composition Acrylic	
PROPERTIES	VALUE	
Glass	2.8 lbs/linear in.	
Polyethylene	1.5	

### **REGULATORY APPROVAL**

RoHS Prop65 REACH

<sup>\*</sup>Please contact your sales representative for details

Yes	Yes	Yes	
TPCH Yes	<b>CPSIA</b> Yes	<b>Direct Food</b> Yes	
Indirect Food Yes			

\*Please contact your sales representative for details

## **LINER**

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

**Type** 9019084

Tensile MD Tensile CD

36 21

 Tear MD
 Tear CD

 61
 71

DESCRIPTION VALUE

Basis Weight 72

Caliper 4.6

## **REGULATORY APPROVAL**

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

**Direct Food** 

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details