Pressure-sensitive adhesives

Acrylic Paper

17" X 22" NATURAL KRAFT / PERMANENT / 80# SCOREBACK L-3

ITEM #SC-053

FACESTOCK

This unbleached brown kraft is smudge resistant, has excellent ink receptivity (inks should be designed to avoid excessive absorption) and is designed for high speed converting. It has excellent perforating, punching and fanfolding characteristics.

Type Paper			
Tensile MD	Tensile CD		
35 Lbs/in	23 Lbs/in		
Tear MD	Tear CD		
116 Grams	132 Grams		
PROPERTIES	VALUE		
Basis Weight	50		
Caliper	5.50 Mil		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	

*Please contact your sales representative for details

ADHESIVE

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Type Permanent	Composition Acrylic		
PROPERTIES	VALUE		
Glass	2.8 lbs/linear in.		
Polyethylene	1.5		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	Direct Food	
Yes	Yes	Yes	

*Please contact your sales representative for details

LINER

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

Туре 9019084				
Tensile MD 36	Tensile CD 21			
Tear MD 61	Tear CD 71			
DESCRIPTION	VALUE			
Basis Weight	72			
Caliper	4.6			
REGULATORY APPROVAL				
RoHS Yes	Prop65 Yes	REACH Yes		
трсн Yes	CPSIA Yes	UL No		
Direct Food No				
*Please contact your sales representative for details				

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG's standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800–358–4448</u> <u>orders.us@beontag.com</u>