

Pressure-sensitive adhesives

Acrylic

Paper

17" X 22" PINK FLUORESCENT / PERMANENT / 80# SCOREBACK L-3

ITEM #SC-057

FACESTOCK

A premium coated one side face stock in a bright fluorescent color with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting.

Туре Paper

Tensile MD Tensile CD 26 Lbs/in 14 Lbs/in **Tear MD Tear CD** 45 Grams 53 Grams

PROPERTIES VALUE

54 # Rm 25 x 38 **Basis Weight**

Caliper 3.80 Mil

REGULATORY APPROVAL

RoHS Prop65 **REACH** Yes Yes Yes **TPCH CPSIA FSC** Yes Yes No

ADHESIVE

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Composition Type Permanent Acrylic

PROPERTIES VALUE

Glass 2.8 lbs/linear in.

Polyethylene 1.5

REGULATORY APPROVAL

RoHS Prop65 REACH Yes Yes Yes

TPCH CPSIA Direct Food Yes Yes Yes

^{*}Please contact your sales representative for details

Indirect Food

Yes

*Please contact your sales representative for details

LINER

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

Туре

9019084

Tensile MD Tensile CD

21 36

Tear MD Tear CD 61 71

DESCRIPTION VALUE

72 **Basis Weight**

Caliper 4.6

REGULATORY APPROVAL

RoHS Prop65 **REACH** Yes Yes Yes **CPSIA TPCH** UL Yes Yes No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details