

Pressure-sensitive adhesives

Acrylic

Paper

17.25" X 22.25" CAST COATED / PERMANENT / 80# ZERO SCORE L-3

ITEM #SC-074

FACESTOCK

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

Туре

Paper

Tensile MDTensile CD25 Lbs/in0 Lbs/inTear MDTear CD35 Grams40 Grams

PROPERTIES

VALUE

Basis Weight

57 # Rm 24 x 26

Caliper

3.70 Mil

REGULATORY APPROVAL

RoHSProp65REACHYesYesYes

TPCHCPSIAULYesYesNo

FSC No

ADHESIVE

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Type Permanent	Composition Acrylic	

PROPERTIES	VALUI
PROPERTIES	VAL

Glass 2.8 lbs/linear in.

Polyethylene 1.5

REGULATORY APPROVAL

RoHSProp65REACHYesYesYes

^{*}Please contact your sales representative for details

Yes	Yes	Pirect Food Yes	
Indirect Food Yes			
*Please contact your sales representative for details			

LINER

0

A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting.

 Type

 9019086

 Tensile MD
 Tensile CD

 51
 0

 Tear MD
 Tear CD

DESCRIPTION VALUE

Basis Weight 72

Caliper 4.6

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details