

Pressure-sensitive adhesives

Acrylic

Paper

# 17.25" X 22.25" MATTE LITHO / PERMANENT / 80# SCOREBACK L-3

# ITEM #SC-002

### **FACESTOCK**

A premium matte litho stock with excellent ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face comes with a brightness of 84% and an opacity of 93%.

**Type**Paper

Tear MDTear CD50 Grams55 Grams

PROPERTIES VALUE

Basis Weight 60lbs/3300 sq ft

Caliper 3.90 Mil

Opacity 93
Brightness 84

# **REGULATORY APPROVAL**

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 Yes
 No

# **ADHESIVE**

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

different substrates.	
<b>Type</b>	Composition
Permanent	Acrylic

PROPERTIES VALUE
------------------

**Glass** 2.8 lbs/linear in.

Polyethylene 1.5

#### **REGULATORY APPROVAL**

RoHS	Prop65	REACH
Yes	Yes	Yes
	00015	

TPCH CPSIA Direct Food Yes Yes

<sup>\*</sup>Please contact your sales representative for details

### **Indirect Food**

Yes

\*Please contact your sales representative for details

# **LINER**

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

Туре

9019084

**Tensile MD Tensile CD** 

21 36

**Tear MD Tear CD** 61 71

**DESCRIPTION VALUE** 

72 **Basis Weight** 

Caliper 4.6

### **REGULATORY APPROVAL**

**RoHS** Prop65 **REACH** Yes Yes Yes **CPSIA TPCH** UL Yes Yes No

**Direct Food** 

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details