

Pressure-sensitive adhesives Latex

Film

# 2 MIL CLEAR ACETATE / AP151 HCWT / 65#FBK L-3

#### ITEM #951771

	<b>○</b> E	ST	$\sim$	$\sim$	7
ГΑ	VΕ	OΙ	U	u	Ν

A 2 mil clear film with excellent ink receptivity and printability.

Type

Film

**Tensile MD** 10000 Psi **Tensile CD** 10000 Psi

**Elong MD** 325

**PROPERTIES** 

**VALUE** 

Caliper

2.00 Mil

**REGULATORY APPROVAL** 

**RoHS** Prop65 Yes Yes **CPSIA TPCH** Yes Yes

**REACH** Yes

**FSC** No

\*Please contact your sales representative for details

### **ADHESIVE**

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type Composition Permanent Latex

**PROPERTIES VALUE** 

5.7 lbs/linear in. **Glass** 

**Polyethylene** 6,5

**REGULATORY APPROVAL** 

Prop65 **REACH RoHS** Yes No Yes

**TPCH CPSIA Direct Food** Yes Yes No

**Indirect Food** 

Yes

\*Please contact your sales representative for details

#### **LINER**

A fully bleached kraft liner which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

Туре	•
1736	35

Tensile MD Tensile CD

33 18

**Tear MD Tear CD** 51 53

DESCRIPTION	VALUE		
Basis Weight	65		
Caliper	3.8		

#### **REGULATORY APPROVAL**

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

## Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details