

Pressure-sensitive adhesives

Rubber

Film

2 MIL CLEAR ACETATE / TL250 @ 2.5 Cwt. / 40#SCK L-3

ITEM #851771

	○ E	ST	\sim	\sim	7
ГΑ	VΕ	OΙ	U	u	Λ

A 2 mil clear film with excellent ink receptivity and printability.

Туре

Film

Tensile MD 10000 Psi Tensile CD 10000 Psi

Elong MD 325

PROPERTIES VALUE

Caliper 2.00 Mil

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 Yes
 No

*Please contact your sales representative for details

ADHESIVE

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

Type Composition Permanent Rubber

PROPERTIES VALUE

Glass 6,7lbs/linear in.

Polyethylene 7,5

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 No
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

Direct Food Indirect Food

No Yes

*Please contact your sales representative for details

LINER

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type 5517342		
Tensile MD	Tensile CD	
34	22	
Tear MD	Tear CD	
32	34	
DESCRIPTION	VALUE	
Basis Weight	40	
Caliper	2.5	
-		
REGUI ATORY APPROVAL		

REGULATORY APPROVAL

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	UL
Yes	Yes	No

Direct Food

No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448

orders.us@beontag.com