

## 2 MIL MATTE WHITE CP POLYESTER TP170 3.2 MIL LASER LINER - T

ITEM #9522

### FACESTOCK

An in-line top coated polyester with a very smooth white finish. It has excellent tear strength, heat resistance, UV resistance and dimensional stability, while the CP top coating allows laser, thermal transfer, silk screen, flexo & letterpress ink receptivity.

**Type**  
Film

**Tensile MD**  
32 Lbs/in

**Tensile CD**  
30 Lbs/in

**Elong CD**  
60

#### PROPERTIES

#### VALUE

**Caliper**

2.00 Mil

**Opacity**

85

#### REGULATORY APPROVAL

**RoHS**  
Yes

**Prop65**  
Yes

**REACH**  
Yes

**TPCH**  
Yes

**CPSIA**  
Yes

**FSC**  
No

\*Please contact your sales representative for details

### ADHESIVE

A general purpose acrylic adhesive showing good initial tack with high shear and high ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

**Type**  
Permanent

**Composition**  
Acrylic

**Shear**  
300

**Min. Application Temperature**  
35 F

**Min. Service Temperature**  
-65 F

**Max. Application Temperature**  
180 F

#### PROPERTIES

#### VALUE

**Stainless Steel**

5.2 lbs/linear in.

**Glass**

3,2lbs/linear in.

**Polyethylene**

1.6

**Corrugated**

1.40 lbs./in.

**Painted Metal**

5.2 lbs/linear in.

**Loop Tack**

2.20 oz/in<sup>2</sup>

**REGULATORY APPROVAL****RoHS**  
Yes**Prop65**  
No**REACH**  
Yes**TPCH**  
Yes**CPSIA**  
Yes**Direct Food**  
No**Indirect Food**  
Yes

\*Please contact your sales representative for details

**LINER**

A bleached kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand die-cutting, marginal punching, perforating, fanfolding and refolding process while providing excellent dimensional stability.

**Type**  
517391**Tensile MD**  
35**Tensile CD**  
15**Tear MD**  
50**Tear CD**  
75**DESCRIPTION****VALUE****Basis Weight**

47

**Caliper**

3.4

**REGULATORY APPROVAL****RoHS**  
Yes**Prop65**  
Yes**REACH**  
Yes**TPCH**  
Yes**CPSIA**  
Yes**UL**  
No**Direct Food**  
No

\*Please contact your sales representative for details

Last update: 02/11/2025

## ADDRESS:

Beontag  
6206 Wolf Creek Pike  
Trotwood, OH 45426  
[800-358-4448](tel:800-358-4448)[orders.us@beontag.com](mailto:orders.us@beontag.com)