

Pressure-sensitive adhesives

Rubber

Film

2 MIL RAINBOW SEAMLESS POLYESTER / TL250 @ 2.5 Cwt. / 50#SCK I-3

ITEM #84217

FACESTOCK

A 2 mil holographic PET film that can be used for a very wide range of label applications because of its excellent mechanical and chemical properties, as well as its dimensional stability. The print surface is top coated to improve printability.

Type Film

 Tensile MD
 Tensile CD

 23 Lbs/in
 23 Lbs/in

 Elong MD
 Elong CD

 118
 118

PROPERTIES VALUE

Caliper 2.00 Mil

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

FSC No

ADHESIVE

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

Type Composition
Permanent Rubber

PROPERTIES VALUE

Glass 6,7lbs/linear in.

Polyethylene 7,5

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 No
 Yes

 TPCH
 CPSIA
 UL

^{*}Please contact your sales representative for details

Yes	Yes	No	
Direct Food No	Indirect Food Yes		
*Please contact your sales re	presentative for details		

LINER

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре			
5517353			
Tensile MD 40	Tensile CD		
	24		
Tear MD	Tear CD		
44	48		
DESCRIPTION	VALUE		
Basis Weight	50		
Caliper	3.2		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
TPCH	CPSIA	UL	
Yes	Yes	No	
Direct Food			
No			
*Please contact your sales repre			

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com