



Pressure-sensitive adhesives

Film

2 MIL WHITE COMPUTER PRINTABLE POLYESTER

ITEM #12095

FACESTOCK A 2 mil white PET film with a top coat designed for dry tone r color laser printing platforms and antistatic functionalit y that improves high quality imaging, transport through presses and post converting processes. Also compatible with scree n, flexo, letterpress/offset and TTR print methods.	
Type Film	
Tensile MD 22000 Psi	Tensile CD 23000 Psi
Elong MD 115	Elong CD 90
PROPERTIES	VALUE
Caliper	2.00 Mil
REGULATORY APPROVAL	
Prop65 Yes	FSC No
*Please contact your sales representative for details	

Last update: 08/22/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com