

2.0 MIL CLEAR PP TC / TP260 / .94 MIL PET

ITEM #98278

FACESTOCK A 2 mil clear biaxially oriented polypropylene with exceptional clarity, excellent die-cut performance and great stiffness. Coated gloss surface is print receptive for standard methods.		
Type Film		
Tensile MD 20,000 psi	Tensile CD 35,000 psi	
Elong MD 180	Elong CD 55%	
PROPERTIES		
Caliper	2.00 Mil	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
FSC No		
*Please contact your sales representative for details		

ADHESIVE A general purpose permanent acrylic adhesive suitable for high speed and high performance labelling machines with excellent adhesion to paper, smooth glass, stainless steel, and PET films.		
Type Perm	Composition Acrylic	
PROPERTIES	VALUE	
Glass	1.5 lbs/linear in.	
Polyethylene	0	
REGULATORY APPROVAL		
RoHS Yes	REACH Yes	TPCH Yes
CPSIA Yes	UL No	Direct Food No

Indirect Food
Yes

FDA 21 CFR 175.105, BfR XIV
No

*Please contact your sales representative for details

LINER

An economical.94 mil clear polyester film liner good for an array of prime label applications.

Type
colacril liner

DESCRIPTION

VALUE

Caliper

0.94 mil

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

*Please contact your sales representative for details

Last update: 08/20/2024

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com