Pressure-sensitive adhesives

Rubber Film

2.3 MIL POLAR WHITE BOPP / TL250 @ 2.5 Cwt. / 40#SCK L-3

ITEM #72225

FACESTOCK

A 2.3 mil white BOPP with a 50% gloss level. Outstanding whiteness and opacity. Topcoated for printability using standard print methods and thermal transfer (with resin ribbon only). This film has high machine direction stiffness and tensile strength for superior high speed label dispensing.

| Туре | | | |
|-------------------------------|---------------------------|-------|--|
| Film | | | |
| Tensile MD | Tensile CD | | |
| 20000 Psi | 35000 Psi | | |
| Elong MD | Elong CD | | |
| 180 | 60 | | |
| PROPERTIES | VALUE | | |
| Caliper | 2.30 Mil | | |
| Opacity | 89 | | |
| REGULATORY APPROVAL | | | |
| RoHS | Prop65 | REACH | |
| Yes | Yes | Yes | |
| ТРСН | CPSIA | UL | |
| Yes | Yes | No | |
| fsc No | | | |
| *Please contact your sales re | epresentative for details | | |

ADHESIVE

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

| Type Permanent | Composition Rubber | |
|--------------------------|------------------------------|---------------------|
| PROPERTIES | VALUE | |
| Glass | 6,7lbs/linear in. | |
| Polyethylene | 7,5 | |
| REGULATORY APPROVAL | | |
| RoHS Yes | Prop65 No | REACH Yes |

| трсн Yes | CPSIA Yes | UL No | |
|-------------------------------|--|--|--|
| Direct Food No | Indirect Food Yes | | |
| *Please contact your sales re | presentative for details | | |
| | ue to its high internal strength it will withsta | le to give a controlled release. This paper has a smo nd all conventional processing operations including | |

| Туре 5517342 | | | |
|--------------------------------|-------------------------|-------|--|
| Tensile MD | Tensile CD | | |
| 34 | 22 | | |
| Tear MD | Tear CD | | |
| 32 | 34 | | |
| DESCRIPTION | VALUE | | |
| Basis Weight | 40 | | |
| Caliper | 2.5 | | |
| REGULATORY APPROVAL | | | |
| RoHS | Prop65 | REACH | |
| Yes | Yes | Yes | |
| ТРСН | CPSIA | UL | |
| Yes | Yes | No | |
| Direct Food No | | | |
| *Please contact your sales rep | resentative for details | | |

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> orders.us@beontag.com