

Pressure-sensitive adhesives

Acrylic

Paper

26" X 20" BRIGHT GOLD LAMINATED FOIL / PERMANENT / 80# ZERO SCORE L-3

ITEM #SC-086

FACESTOCK

A 60# acrylic topcoated foil paper that accepts water base and solvent base inks and can be embossed.

Type Paper

Tensile MDTensile CD36 Lbs/in23 Lbs/inTear MDTear CD50 Grams51 Grams

PROPERTIES VALUE

Basis Weight 60 # Rm 25 x 38

Caliper 3.60 Mil

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 No
 No

ADHESIVE

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Туре	Composition
Permanent	Acrylic

PROPERTIES	VALUE

Glass 2.8 lbs/linear in.

Polyethylene 1.5

REGULATORY APPROVAL

RoHS	Prop65	REACH
Yes	Yes	Yes

TPCH CPSIA Direct Food Yes Yes

^{*}Please contact your sales representative for details

Indirect Food

Yes

*Please contact your sales representative for details

LINER

A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting.

Туре
9019086

Tensile MD Tensile CD

51 (

Tear MD Tear CD

DESCRIPTION VALUE

Basis Weight 72

Caliper 4.6

REGULATORY APPROVAL

RoHS Prop65 REACH
Yes Yes Yes

TPCHCPSIAULYesYesNo

Direct Food

No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com