

Pressure-sensitive adhesives

Acrylic

Paper

26" X 20" MATTE LITHO / PERMANENT / 80# ZERO SCORE L-3

ITEM #SC-072

FACESTOCK

A premium matte litho stock with excellent ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face comes with a brightness of 84% and an opacity of 93%.

Туре Paper

Tear MD Tear CD 50 Grams 55 Grams

PROPERTIES VALUE

Basis Weight 60lbs/3300 sq ft

Caliper 3.90 Mil

93 **Opacity Brightness** 84

REGULATORY APPROVAL

REACH RoHS Prop65 Yes Yes Yes **TPCH CPSIA** FSC Yes Yes No

ADHESIVE

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many

different substrates.			
Type Permanent	Composition Acrylic		

PROPERTIES	VALUE

Glass 2.8 lbs/linear in.

Polyethylene 1.5

REGULATORY APPROVAL

RoHS	Prop65	REACH
Yes	Yes	Yes

TPCH CPSIA Direct Food Yes Yes Yes

^{*}Please contact your sales representative for details

Indirect Food

Yes

*Please contact your sales representative for details

LINER

A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting.

Туре
9019086

Tensile MD Tensile CD

51 (

Tear MD Tear CD ()

Basis Weight 72

Caliper 4.6

REGULATORY APPROVAL

RoHS Prop65 REACH
Yes Yes Yes

TPCHCPSIAULYesYesNo

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details