Pressure-sensitive adhesives

Acrylic Paper

26" X 40" BRIGHT WHITE GLOSS / PERMANENT / 80# SCOREBACK L-3

ITEM #SC-306

FACESTOCK A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity. Туре Paper **Tensile MD Tensile CD** 35 Lbs/in 19 Lbs/in Tear MD Tear CD 47 Grams 46 Grams PROPERTIES VALUE **Basis Weight** 60 # Rm 25 x 38 3.20 Mil Caliper 88 Opacity **Brightness** 90 **REGULATORY APPROVAL** RoHS Prop65 REACH Yes Yes Yes CPSIA FSC трсн Yes Yes No *Please contact your sales representative for details

ADHESIVE

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Type Permanent	Composition Acrylic	
PROPERTIES	VALUE	
Glass	2.8 lbs/linear in.	
Polyethylene	1.5	
REGULATORY APPROVAL RoHS	Prop65	REACH

Yes	Yes	Yes
трсн Yes	CPSIA Yes	Direct Food Yes
Indirect Food Yes		

*Please contact your sales representative for details

LINER

This liner is clay-coated bleached kraft designed for roll-to-sheet applications. It is manufactured with scores every 1.25\" apart.

Туре 9019084				
Tensile MD	Tensile CD			
36	21			
Tear MD	Tear CD			
61	71			
DESCRIPTION	VALUE			
Basis Weight	72			
Caliper	4.6			
REGULATORY APPROVAL				
RoHS	Prop65	REACH		
Yes	Yes	Yes		
ТРСН	CPSIA	UL		
Yes	Yes	No		
Direct Food No				
*Please contact your sales representative for details				

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG's standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>