

3 MIL FROSTY CLEAR POLYOLEFIN TR447 65#FBK

ITEM #99207

<b>FACESTOCK</b> A 3.0 mil frosty clear polyolefin that has been corona treated for maximum performance when printing with UV, Letterpress, Standard or Water based inks.			
<b>Type</b> Film			
<b>Tensile MD</b> 6,000		<b>Tensile CD</b> 4,500 psi	
<b>Tear MD</b> 150		<b>Tear CD</b> 150g	
<b>Elong MD</b> 550		<b>Elong CD</b> 550	
<b>PROPERTIES</b>		<b>VALUE</b>	
<b>Caliper</b>		3.0 mil	
<b>REGULATORY APPROVAL</b>			
<b>RoHS</b> Yes		<b>Prop65</b> Yes	
<b>TPCH</b> Yes		<b>REACH</b> Yes	
		<b>FSC</b> No	
*Please contact your sales representative for details			

<b>ADHESIVE</b> A general purpose, removable rubber based emulsion adhesive featuring good initial tack and moderate adhesion. It has limited plasticizer, UV and solvent resistance. This is a standard removable adhesive for tape reels, computer disks and kids stickers.		
<b>Type</b> Removable	<b>Composition</b> Latex	<b>Shear</b> 40
<b>Min. Application Temperature</b> 40 F	<b>Min. Service Temperature</b> 1 F	<b>Max. Application Temperature</b> 120 F
<b>PROPERTIES</b>	<b>VALUE</b>	
<b>Stainless Steel</b>	2.5 lbs/linear in.	
<b>Glass</b>	0,9lbs/linear in.	
<b>Polyethylene</b>	1,8	
<b>Corrugated</b>	1.00 lbs./in.	
<b>Painted Metal</b>	1.6 lbs/linear in.	

Loop Tack	1.50 oz/in <sup>2</sup>
-----------	-------------------------

**REGULATORY APPROVAL**

<b>RoHS</b> Yes	<b>Prop65</b> No	<b>REACH</b> Yes
--------------------	---------------------	---------------------

\*Please contact your sales representative for details

**LINER**

A fully bleached kraft liner which has been silicone coated one side to give a controlled release. This paper has high internal strength top withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

<b>Type</b> 47365	<b>Tensile MD</b> 33	<b>Tensile CD</b> 18
----------------------	-------------------------	-------------------------

DESCRIPTION	VALUE
-------------	-------

Basis Weight	65
--------------	----

Caliper	3.8
---------	-----

**REGULATORY APPROVAL**

<b>RoHS</b> Yes	<b>Prop65</b> Yes	<b>REACH</b> Yes
--------------------	----------------------	---------------------

\*Please contact your sales representative for details

Last update: 02/11/2025

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag  
6206 Wolf Creek Pike  
Trotwood, OH 45426

800-358-4448

[orders.us@beontag.com](mailto:orders.us@beontag.com)