

Pressure-sensitive adhesives

Rubber

Film

3.6 MIL POLYART / TL250 @ 2.5 Cwt. / 50#SCK L-3

ITEM #78000

FACESTOCK

A high performance polyethylene base synthetic paper with a unique computer printable top coating allowing Polyart to be printed with flexo, litho, gravure, letterpress and screen methods. It can also be used with thermal transfer, ion dep and dot matrix.

Туре

Film

Tensile MD
6670 Psi
5510 Psi

Tear MD
496 Grams
599 Grams
Elong MD
Elong CD
110

PROPERTIES VALUE

Opacity 90

REGULATORY APPROVAL

Caliper

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 No
 No

3.60 Mil

*Please contact your sales representative for details

ADHESIVE

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

TypeCompositionPermanentRubber

PROPERTIES VALUE

Glass 6,7lbs/linear in.

Polyethylene 7,5

REGULATORY APPROVAL

RoHSProp65REACHYesNoYes

TPCH	CPSIA	UL
Yes	Yes	No

Direct Food Indirect Food

No Yes

LINER

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре
5517353

Tensile MD Tensile CD

24 40

Tear CD **Tear MD** 44 48

DESCRIPTION	VALUE
Basis Weight	50
Caliper	3.2

REGULATORY APPROVAL

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	ul
Yes	Yes	No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details