

Pressure-sensitive adhesives

Acrylic

Paper

#4 ESTATE WHITE / TS585WS @ 1.6 Cwt. / 1.2 MIL PET L-3

ITEM #87665

FACESTOCK

Estate label is an uncoated face stock, wet strength grade, which meets the demanding packaging needs of the wine industry. The estate label combines prestige appearance with sophisticated production properties that ensure smooth performance on many high speed presses.

Type

Paper

| PROPERTIES | VALUE |
|--------------|----------|
| Basis Weight | 60 |
| Caliper | 5.50 Mil |
| Opacity | 93 |
| Brightness | 87 |
| | |

REGULATORY APPROVAL

| RoHS | Prop65 | REACH | |
|-------------|---------------|--------------|--|
| Yes | Yes | Yes | |
| TPCH | CPSIA | UL | |
| Yes | Yes | No | |

FSC No

ADHESIVE

Painted Metal

A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.

| Type Permanent | Composition Acrylic | Shear 65 |
|---------------------------------------|--|---------------------------------------|
| Min. Application Temperature -20 F | Min. Service Temperature -65 F | Max. Application Temperature 140 F |
| PROPERTIES | VALUE | |
| Stainless Steel | 4.8 lbs/linear in. | |
| Glass | 3,2lbs/linear in. | |
| Polyethylene | 6,5lbs/linear in. | |
| Corrugated | 1.45 lbs./in. | |

4.4 lbs/linear in.

^{*}Please contact your sales representative for details

Loop Tack 2.70 oz/in² **REGULATORY APPROVAL RoHS** Prop65 REACH Yes No Yes **TPCH CPSIA Direct Food** Yes Yes No **Indirect Food** Yes *Please contact your sales representative for details

| LINER | | | | | | | |
|---|------------|-------|--|--|--|--|--|
| An economical 1.2 mil clear polyester film liner good for an array of prime label applications. | | | | | | | |
| Tensile MD | Tensile CD | | | | | | |
| 30000 | 0 | | | | | | |
| Tear MD | Tear CD | | | | | | |
| 0 | 0 | | | | | | |
| DESCRIPTION | VALUE | | | | | | |
| Basis Weight | 0 | | | | | | |
| Caliper | 1,2 | | | | | | |
| REGULATORY APPROVAL | | | | | | | |
| RoHS | Prop65 | REACH | | | | | |
| Yes | Yes | Yes | | | | | |
| TPCH | CPSIA | | | | | | |
| Yes | Yes | | | | | | |

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com