

Pressure-sensitive adhesives

Acrylic

Film

# 4 MIL FLEXIBLE NTC VINYL / TS523 @ 1.5 Cwt. / 100# TAG L-3

## ITEM #4898

## **FACESTOCK**

A 4 Mil white non top coated vinyl with polymeric plasticizers, formulated to provide optimum performance with pressure sensitive adhesives.

Туре

Film

Tensile MDTensile CD3900 lb/in3800 lb/inTear MDTear CD100 Grams100 Grams

PROPERTIES VALUE

Caliper 4.0

**REGULATORY APPROVAL** 

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 Yes
 No

# **ADHESIVE**

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

TypeCompositionShearPermanentAcrylic350

Min. Application Temperature Min. Service Temperature Max. Application Temperature

35 F -65 F 200 F

PROPERTIES VALUE

Stainless Steel5.6 lbs/linear in.Glass2,8lbs/linear in.

Polyethylene 2.9

Corrugated 1.50 lbs./in.

Painted Metal 4.9 lbs/linear in.

**Loop Tack** 2.70 oz/in<sup>2</sup>

<sup>\*</sup>Please contact your sales representative for details

#### **REGULATORY APPROVAL**

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes

**Indirect Food** 

Yes

\*Please contact your sales representative for details

## **LINER**

A 100# tag liner which has been silicone coated one side to give a controlled release. It has exceptionally high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

No

Tensile MD Tensile CD

70 32

**Tear MD Tear CD** 130 160

**DESCRIPTION** VALUE

**Basis Weight** 0

Caliper 8

# **REGULATORY APPROVAL**

RoHSProp65REACHYesYesYes

TPCH CPSIA
Yes Yes

\*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com