

Pressure-sensitive adhesives

Acrylic

Film

4 MIL FLEXIBLE TC VINYL / TR440 @ 1.0 Cwt. / 65#FBK L-3

ITEM #54085

FACESTOCK

A 4 mil flexible white vinyl with polymeric plasticizers, formulated to provide optimum performance with pressure sensitive adhesives. The top-coating provides outstanding adhesion to various printing inks.

Туре

Film

Tensile MDTensile CD3900 lb/in3800 lb/inTear MDTear CD100 Grams100 Grams

PROPERTIES VALUE

Caliper 4.0

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 Yes
 No

ADHESIVE

A specialty clear acrylic adhesive showing good initial removable tack with high shear and high removable adhesion. This adhesive has excellent clarity & minimum cold flow. Good removability on a wide range of substrates including corrugated and many plastic surfaces.

TypeCompositionShearRemovableAcrylic110

Min. Application Temperature Min. Service Temperature Max. Application Temperature

40 F -65 F 150 F

PROPERTIES VALUE

Stainless Steel 4.7 lbs/linear in.

Glass 3lbs/linear in.

Polyethylene 1.4

Corrugated 1.20 lbs./in.

Painted Metal 4.2 lbs/linear in.

Loop Tack 1.70 oz/in²

^{*}Please contact your sales representative for details

REGULATORY APPROVAL

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com