Pressure-sensitive adhesives

Acrylic Paper

55# HIBRIGHT SemiGloss / AT150 @ 1.3 CWT / 1.2 MIL PET



ITEM #74231

FACESTOCK A premium semigloss calendar coated one side stock with excellent ink receptivity and print characteristics. This stock offers an 88% brightness, has an 87% opacity and a 70% gloss rating					
Туре					
Paper					
Tensile MD	Tensile CD				
35 Lbs/in	16 Lbs/in				
Tear MD	Tear CD				
35 Grams	35 Grams				
PROPERTIES	VALUE				
Basis Weight	55				
Caliper	2.80 Mil				
REGULATORY APPROVAL					
RoHS	Prop65	REACH			
Yes	Yes	Yes			
ТРСН	CPSIA	FSC			
Yes	Yes	Yes			

ADHESIVE

An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 °F. Very good plasticizer, UV and solvent resistance. AT150 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps

Type Permanent	Composition Acrylic	Shear 100
Min. Application Temperature -20 F	Min. Service Temperature -65 F	Max. Application Temperature 160 F
PROPERTIES	VALUE	
PROPERTIES Stainless Steel	VALUE 5.1 lbs/linear in.	

Corrugated	1.50 lbs./in.		
Painted Metal	4.9 lbs/linear in.		
Loop Tack	2.90 oz/in ²		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	Direct Food	
Yes	Yes	No	
Indirect Food			
Yes			
*Please contact your sales repr	recentative for dataile		

LINER

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile MD	Tensile CD		
30000	0		
Tear MD	Tear CD		
0	0		
DESCRIPTION	VALUE		
Basis Weight	0		
Caliper	1,2		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA		
Yes	Yes		
*Please contact your sales rep	resentative for details		

Last update: 08/21/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG's standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG's shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>