

Pressure-sensitive adhesives

Acrylic

Paper

55# HIBRIGHT SEMIGLOSS / IP400 @ 1.7 Cwt. / 44#PK L-4

ITEM #88073

FACESTOCK

A premium semigloss calendar coated one side stock with excellent ink receptivity and print characteristics. This stock offers an 88% brightness has an 87% opacity and a 70% gloss rating.

Туре	
Paper	

Tensile MD Tensile CD
35 Lbs/in 16 Lbs/in

Tear MD Tear CD
35 Grams 38 Grams

PROPERTIES	VALUE
Basis Weight	55
Caliper	2.80 Mil
Opacity	87
Brightness	88

REGULATORY APPROVAL

RoHSProp65REACHYesYesYes
TPCH
Yes
Yes
No

ADHESIVE

Corrugated

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

Type Permanent	Composition Acrylic	Shear 80
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 200 F
PROPERTIES	VALUE	
PROPERTIES Stainless Steel	VALUE 5.5 lbs/linear in.	

1.45 lbs./in.

^{*}Please contact your sales representative for details

Painted Metal 3.0 lbs/linear in.

Loop Tack 5.00 oz/in²

REGULATORY APPROVAL

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

*Please contact your sales representative for details

LINER

A medium weight natural kraft coated 1 side (C1S) with a gloss polyethylene. Silicone coating has been added on the gloss side (C1S) for a controlled release. It has superb smoothness, excellent dimensional stability and exceptional layflat characteristics.

Type 17745

 Tensile MD
 Tensile CD

 35 Lbs/In
 13 Lbs/in

 Tear MD
 Tear CD

 30 Grams
 50 Grams

DESCRIPTION VALUE

Basis Weight 44 Lbs/Rm

Caliper 3.1 Mil

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

Direct Food

No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com