



Pressure-sensitive adhesives

Acrylic

Paper

60# BLACK CHROMECAST / IP400 @ 1.7 Cwt. / 44#PK L-4

ITEM #78857

FACESTOCK A 60# high gloss, C1S, Black paper that exhibits superior graphic affect for beverage and food Products.	
Type Paper	
Tensile MD 30 Lbs/in	Tensile CD 19 Lbs/in
Tear MD 55 Grams	Tear CD 60 Grams
PROPERTIES	VALUE
Basis Weight	60
Caliper	4.00 Mil
Opacity	99
REGULATORY APPROVAL FSC No *Please contact your sales representative for details	

ADHESIVE A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.		
Type Permanent	Composition Acrylic	Shear 80
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 200 F
PROPERTIES	VALUE	
Stainless Steel	5.5 lbs/linear in.	
Glass	3,2lbs/linear in.	
Polyethylene	2	
Corrugated	1.45 lbs./in.	
Painted Metal	3.0 lbs/linear in.	
Loop Tack	5.00 oz/in ²	

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

Direct Food
No

Indirect Food
Yes

*Please contact your sales representative for details

LINER

A medium weight natural kraft coated 1 side (C1S) with a gloss polyethylene. Silicone coating has been added on the gloss side (C1S) for a controlled release. It has superb smoothness, excellent dimensional stability and exceptional layflat characteristics.

Type
17745

Tensile MD
35 Lbs/In

Tensile CD
13 Lbs/in

Tear MD
30 Grams

Tear CD
50 Grams

DESCRIPTION

VALUE

Basis Weight

44 Lbs/Rm

Caliper

3.1 Mil

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com