

60# CLASSIC NATURAL WHITE FELT WS / TS585WS @ 1.6 Cwt. / 1.2 MIL PET L-3

ITEM #78878

FACESTOCK This 60# text weight natural white felt paper features great ink holdout and glue adhesion.		
Type Paper		
Tensile MD 8 Lbs/in	Tensile CD 6 Lbs/in	
PROPERTIES		
Basis Weight	60 # Rm 25 x 38	
Caliper	4.40 Mil	
Opacity	90	
Brightness	79	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	FSC No
*Please contact your sales representative for details		

ADHESIVE A specialty adhesive designed to adhere to slightly wet surfaces with good ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for hard to label substrates.		
Type Permanent	Composition Acrylic	Shear 65
Min. Application Temperature -20 F	Min. Service Temperature -65 F	Max. Application Temperature 140 F
PROPERTIES	VALUE	
Stainless Steel	4.8 lbs/linear in.	
Glass	3,2lbs/linear in.	
Polyethylene	6,5lbs/linear in.	
Corrugated	1.45 lbs./in.	
Painted Metal	4.4 lbs/linear in.	

Loop Tack			2.70 oz/in ²
REGULATORY APPROVAL			
RoHS Yes	Prop65 No	REACH Yes	
TPCH Yes	CPSIA Yes	Direct Food No	
Indirect Food Yes			
*Please contact your sales representative for details			

LINER		
An economical 1.2 mil clear polyester film liner good for an array of prime label applications.		
Tensile MD 30000	Tensile CD 0	
Tear MD 0	Tear CD 0	
DESCRIPTION	VALUE	
Basis Weight	0	
Caliper	1,2	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	
*Please contact your sales representative for details		

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com