

Pressure-sensitive adhesives

Acrylic

Paper

60# ULTRA WHITE SemiGloss / AT150 @ 1.3 Cwt. / 2.5 MIL SCK L-3

ITEM #78138

FACESTOCK

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity.

Type
Paper

Tensile MDTensile CD35 Lbs/in19 Lbs/inTear MDTear CD47 Grams46 Grams

PROPERTIES	VALUE
Basis Weight	60 # Rm 25 x 38
Caliper	3.20 Mil
Opacity	88
Brightness	90

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 FSC

 Yes
 No
 No

ADHESIVE

Corrugated

An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as $-20\,^{\circ}$ F. Very good plasticizer, UV and solvent resistance. AT150 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps

Type Permanent Min. Application Temperature	Composition Acrylic Min. Service Temperature	Shear 100 Max. Application Temperature
-20 F PROPERTIES	-65 F VALUE	160 F
Stainless Steel	5.1 lbs/linear in.	
Glass	4,4 lbs/linear in.	

1.50 lbs./in.

^{*}Please contact your sales representative for details

Painted Metal 4.9 lbs/linear in.

Loop Tack 2.90 oz/in²

REGULATORY APPROVAL

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com