

Pressure-sensitive adhesives

Acrylic

Paper

# 60# ULTRA WHITE SemiGloss / TR1 @ 1.0 Cwt. / 40#SCK L-5

#### ITEM #79231

#### **FACESTOCK**

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity.

**Type**Paper

Tensile MDTensile CD35 Lbs/in19 Lbs/inTear MDTear CD47 Grams46 Grams

PROPERTIES	VALUE
Basis Weight	60 # Rm 25 x 38
Caliper	3.20 Mil
Opacity	88
Brightness	90

# REGULATORY APPROVAL

RoHS<br/>YesProp65<br/>YesREACH<br/>YesTPCH<br/>YesCPSIA<br/>YesFSC<br/>No

## **ADHESIVE**

A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.

Туре	Composition	Shear
Removable	Acrylic	35

Min. Application Temperature Min. Service Temperature Max. Application Temperature

40 F -65 F 120 F

PROPERTIES	VALUE
Stainless Steel	1.8 lbs/linear in.
Glass	Olbs/linear in.
Corrugated	0.55 lbs./in.
Painted Metal	1.3 lbs/linear in.

**Loop Tack** 

<sup>\*</sup>Please contact your sales representative for details

## 1.35 oz/in<sup>2</sup>

#### **REGULATORY APPROVAL**

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes No

**Indirect Food** 

Yes

## **LINER**

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Tensile MD Tensile CD 34 22

 Tear MD
 Tear CD

 32
 34

DESCRIPTION VALUE

Basis Weight 40

Caliper 2,5

## **REGULATORY APPROVAL**

RoHSProp65REACHYesYesYes

TPCH CPSIA
Yes Yes

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details

<sup>\*</sup>Please contact your sales representative for details