

60# ULTRA WHITE SEMIGLOSS / TR447 / 3.4 MIL LAYFLAT L-3

ITEM #78118

<div>FACESTOCK</div> <div>A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity.</div>		
<div>Type</div> <div>Paper</div>		
<div>Tensile MD</div> <div>35 Lbs/in</div>	<div>Tensile CD</div> <div>19 Lbs/in</div>	
<div>Tear MD</div> <div>47 Grams</div>	<div>Tear CD</div> <div>46 Grams</div>	
<div>PROPERTIES</div>	<div>VALUE</div>	
<div>Basis Weight</div>	<div>60 # Rm 25 x 38</div>	
<div>Caliper</div>	<div>3.20 Mil</div>	
<div>Opacity</div>	<div>88</div>	
<div>Brightness</div>	<div>90</div>	
<div>REGULATORY APPROVAL</div>		
<div>RoHS</div> <div>Yes</div>	<div>Prop65</div> <div>Yes</div>	<div>REACH</div> <div>Yes</div>
<div>TPCH</div> <div>Yes</div>	<div>CPSIA</div> <div>Yes</div>	<div>FSC</div> <div>No</div>
<div>*Please contact your sales representative for details</div>		

ADHESIVE A general purpose, removable rubber based emulsion adhesive featuring good initial tack and moderate adhesion. It has limited plasticizer, UV and solvent resistance. This is a standard removable adhesive for tape reels, computer disks and kids stickers.		
Type Removable	Composition Latex	Shear 40
Min. Application Temperature 40 F	Min. Service Temperature 1 F	Max. Application Temperature 120 F
PROPERTIES	VALUE	
Stainless Steel	2.5 lbs/linear in.	
Glass	0,9lbs/linear in.	
Polyethylene	1,8	
Corrugated	1.00 lbs./in.	
Painted Metal		

1.6 lbs/linear in.

Loop Tack

1.50 oz/in²

REGULATORY APPROVAL

RoHS
Yes

Prop65
No

REACH
Yes

TPCH
Yes

CPSIA
Yes

Direct Food
No

Indirect Food
Yes

*Please contact your sales representative for details

LINER

A bleached kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand die-cutting, marginal punching, perforating, fanfolding and refolding process while providing excellent dimensional stability.

Type
517391

Tensile MD
35

Tensile CD
15

Tear MD
50

Tear CD
75

DESCRIPTION

VALUE

Basis Weight

47

Caliper

3.4

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

*Please contact your sales representative for details

Last update: 08/22/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com