

65# PREMIUM MATTE WHITE INKJET / TP170 @ 1.3 Cwt. / 50#SCK L-3

ITEM #98138

FACESTOCK A premium matte-coated photo grade paper offering universal compatibility with a wide range of water based ink jet printing technologies. The paper offers instant-dry properties, outstanding contrasts, high resolution print performance and improved waterfastness vs. standard matte grades.											
Type Paper											
<table><tr><th>PROPERTIES</th><th colspan="2">VALUE</th></tr><tr><td>Basis Weight</td><td colspan="2">65</td></tr><tr><td>Caliper</td><td colspan="2">5.00 Mil</td></tr></table>			PROPERTIES	VALUE		Basis Weight	65		Caliper	5.00 Mil	
PROPERTIES	VALUE										
Basis Weight	65										
Caliper	5.00 Mil										
REGULATORY APPROVAL											
RoHS Yes	Prop65 Yes	REACH Yes									
TPCH Yes	CPSIA Yes	FSC No									
*Please contact your sales representative for details											

ADHESIVE A general purpose acrylic adhesive showing good initial tack with high shear and high ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.		
Type Permanent	Composition Acrylic	Shear 300
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 180 F
PROPERTIES	VALUE	
Stainless Steel	5.2 lbs/linear in.	
Glass	3,2lbs/linear in.	
Polyethylene	1.6	
Corrugated	1.40 lbs./in.	
Painted Metal	5.2 lbs/linear in.	
Loop Tack	2.20 oz/in²	
REGULATORY APPROVAL		

RoHS Yes	Prop65 No	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food No
Indirect Food Yes		
*Please contact your sales representative for details		

LINER

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type 5517353	
Tensile MD 40	Tensile CD 24
Tear MD 44	Tear CD 48

DESCRIPTION	VALUE
Basis Weight	50
Caliper	3.2

REGULATORY APPROVAL

RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No		

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com