Pressure-sensitive adhesives

Paper

80# SemiGloss / AP151 @ 1.3 Cwt. / 40#SCK L-3

Latex

ITEM #86663

FACESTOCK

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 89% brightness and an 92% opacity.

Type Paper			
PROPERTIES	VALUE		
Basis Weight	80 # Rm 25 x 38		
Caliper	4.20 Mil		
Opacity	93		
Brightness	83		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	FSC	
Yes	Yes	No	
*Please contact your sales rep	resentative for details		

ADHESIVE

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type Permanent	Composition Latex	Shear 80
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 220 F
PROPERTIES	VALUE	
Stainless Steel	7.3 lbs/linear in.	
Glass	5.7 lbs/linear in.	
Polyethylene	6.5	
Corrugated	2.50 lbs./in.	
Painted Metal	7.0 lbs/linear in.	
Loop Tack	5.00 oz/in ²	

REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	No	Yes	
трсн	CPSIA	Direct Food	
Yes	Yes	No	

*Please contact your sales representative for details

LINER

A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.

Туре 5517342			
Tensile MD 30 Lbs/In	Tensile CD 20 Lbs/In		
Tear MD 32 Grams	Tear CD 34 Grams		
DESCRIPTION	VALUE		
Basis Weight	40.5 Lbs/Rm		
Caliper	2.5 Mil		
REGULATORY APPROVAL			
RoHS Yes	Prop65 Yes	REACH Yes	
трсн Yes	CPSIA Yes	UL No	
Direct Food No			
*Please contact your sales repres	entative for details		

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG's standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>