

Bright Silver Metallized Paper / AT333 @ 1.30 Cwt. / 40#SCK L-3

ITEM #5805

FACESTOCK A bright silver paper facestock. A reflective, acrylic lacquer coated metallized paper facestock for excellent flexographic print results.		
Type Paper		
PROPERTIES		VALUE
Basis Weight		56 # Rm 25 x 38
Caliper		2.60 Mil
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	FSC No
*Please contact your sales representative for details		

ADHESIVE An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT333 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps.		
Type Permanent	Composition Acrylic	Shear 60
Min. Application Temperature -20 F	Min. Service Temperature -65 F	Max. Application Temperature 160 F
PROPERTIES	VALUE	
Stainless Steel	4.7 lbs/linear in.	
Glass	1,3lbs/linear in.	
Polyethylene	2.2	
Corrugated	1.40 lbs./in.	
Painted Metal	4.4 lbs/linear in.	
Loop Tack	2.20 oz/in²	
REGULATORY APPROVAL		
RoHS	Prop65	REACH

Yes	No	Yes
TPCH Yes	CPSIA Yes	Direct Food No
Indirect Food Yes		
*Please contact your sales representative for details		

LINER Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.											
Type 5517342											
Tensile MD 34	Tensile CD 22										
Tear MD 32	Tear CD 34										
DESCRIPTION	VALUE										
Basis Weight	40										
Caliper	2.5										
REGULATORY APPROVAL <table> <tr> <td>RoHS Yes</td><td>Prop65 Yes</td><td>REACH Yes</td></tr> <tr> <td>TPCH Yes</td><td>CPSIA Yes</td><td>UL No</td></tr> <tr> <td>Direct Food No</td><td></td><td></td></tr> </table>			RoHS Yes	Prop65 Yes	REACH Yes	TPCH Yes	CPSIA Yes	UL No	Direct Food No		
RoHS Yes	Prop65 Yes	REACH Yes									
TPCH Yes	CPSIA Yes	UL No									
Direct Food No											
*Please contact your sales representative for details											

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
 Beontag
 6206 Wolf Creek Pike
 Trotwood, OH 45426
 800-358-4448
orders.us@beontag.com