

Pressure-sensitive adhesives

Rubber

Paper

BRIGHT WHITE EDP / TL250 @ 2.5 Cwt. / 40#SCK L-3

ITEM #4404412

FACESTOCK

A white uncoated litho designed with smudge resistance for high speed converting while having excellent perforating, punching and fanfolding characteristics. This stock also offers 88% in brightness and 83% opacity.

TypePaper

Tensile MD Tensile CD 40 Lbs/in 20 Lbs/in

Tear MD Tear CD 50 Grams

PROPERTIES	VALUE
Basis Weight	50 # Rm 25 x 38
Caliper	3.50 Mil
Opacity	85
Brightness	88

REGULATORY APPROVAL

Prop65 FSC Yes No

ADHESIVE

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

Туре	Composition
Permanent	Rubber

PROPERTIES	VALUE
PROPERTIES	VALUE

Glass 6,7lbs/linear in.

Polyethylene 7,5

REGULATORY APPROVAL

RoHS	Prop65	REACH
Yes	No	Yes
трсн	CPSIA	ul
Yes	Yes	No

^{*}Please contact your sales representative for details

Direct Food Indirect Food No Yes

*Please contact your sales representative for details

LINER

A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.

Type 5517342

Tensile MD Tensile CD
30 Lbs/ln 20 Lbs/ln

Tear MD Tear CD
32 Grams 34 Grams

DESCRIPTION VALUE

Basis Weight 40.5 Lbs/Rm

Caliper 2.5 Mil

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details