

BRIGHT WHITE EDP / TS523 @ 1.5 Cwt. / 1.5 MIL PET L-3

ITEM #4489645

FACESTOCK A white uncoated litho designed with smudge resistance for high speed converting while having excellent perforating, punching and fanfolding characteristics. This stock also offers 88% in brightness and 83% opacity.	
Type Paper	
Tensile MD 40 Lbs/in	Tensile CD 20 Lbs/in
Tear MD 45 Grams	Tear CD 50 Grams
PROPERTIES	VALUE
Basis Weight	50 # Rm 25 x 38
Caliper	3.50 Mil
Opacity	85
Brightness	88
REGULATORY APPROVAL	
Prop65 Yes	FSC No
*Please contact your sales representative for details	

ADHESIVE A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.		
Type Permanent	Composition Acrylic	Shear 350
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 200 F
PROPERTIES	VALUE	
Stainless Steel	5.6 lbs/linear in.	
Glass	2,8lbs/linear in.	
Polyethylene	2.9	
Corrugated	1.50 lbs./in.	
Painted Metal	4.9 lbs/linear in.	

<div> <div>Loop Tack</div> <div>2.70 oz/in²</div> </div>		
<div>REGULATORY APPROVAL</div> <div> <div> <div>RoHS</div> <div>Yes</div> </div> <div> <div>Prop65</div> <div>No</div> </div> <div> <div>REACH</div> <div>Yes</div> </div> </div> <div> <div> <div>TPCH</div> <div>Yes</div> </div> <div> <div>CPSIA</div> <div>Yes</div> </div> <div> <div>Direct Food</div> <div>No</div> </div> </div> <div> <div>Indirect Food</div> <div>Yes</div> </div> <div>*Please contact your sales representative for details</div>		

<div>LINER</div> <div>A 1.5 mil polyester liner which has been silicone coated one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end usage, making it an outstanding liner for high speed, automatic applications.</div>	
<div> <div>Type</div> <div>619827</div> </div> <div> <div>Tensile MD</div> <div>32000</div> </div> <div> <div>Tensile CD</div> <div>0</div> </div> <div> <div>Tear MD</div> <div>0</div> </div> <div> <div>Tear CD</div> <div>0</div> </div>	
DESCRIPTION	VALUE
Caliper	1.5
<div>REGULATORY APPROVAL</div> <div> <div> <div>RoHS</div> <div>Yes</div> </div> <div> <div>Prop65</div> <div>Yes</div> </div> <div> <div>REACH</div> <div>Yes</div> </div> </div> <div> <div> <div>TPCH</div> <div>Yes</div> </div> <div> <div>CPSIA</div> <div>Yes</div> </div> <div> <div>UL</div> <div>No</div> </div> </div> <div> <div>Direct Food</div> <div>No</div> </div> <div>*Please contact your sales representative for details</div>	

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
 Beontag
 6206 Wolf Creek Pike
 Trotwood, OH 45426
 800-358-4448
orders.us@beontag.com