

Pressure-sensitive adhesives

Acrylic

## \*\*\*FREE-FILM\*\*\* 40#SCK L-3 TS523 4.5 MIL LF L-10

## ITEM #59017

## **ADHESIVE**

35 F

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

200 F

TypeCompositionShearPermanentAcrylic350

Min. Application Temperature Min. Service Temperature Max. Application Temperature

-65 F

PROPERTIES VALUE

**Stainless Steel** 5.6 lbs/linear in.

**Glass** 2,8lbs/linear in.

Polyethylene 2.9

**Corrugated** 1.50 lbs./in.

Painted Metal 4.9 lbs/linear in.

Loop Tack 2.70 oz/in<sup>2</sup>

**REGULATORY APPROVAL** 

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes No

**Indirect Food** 

Yes

\*Please contact your sales representative for details

## **LINER**

A clay coated kraft liner which has been silicone coated one side to give a controlled release. It is designed to withstand all diecutting, margin punching, perforating, fanfolding and refolding processes. It is an excellent layflat liner.

Туре

517165

Tensile MD Tensile CD

51 0

 Tear MD
 Tear CD

 0
 100

**DESCRIPTION** VALUE

<b>Basis Weight</b>	72		
Caliper	4.6		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
TPCH	CPSIA	UL	
Yes	Yes	No	
Direct Food			
No			
*Please contact your sales	representative for details		
*Please contact your sales representative for details			

Last update: 08/22/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com