

Pressure-sensitive adhesives

Acrylic

Paper

FREE-FILM 40#SCK TS523 2.5 MIL LAYFLAT L-5



ITEM #8823

FACESTOCK

A premium semigloss calendar coated one side stock with excellent ink receptivity and print characteristics. This stock offers an 88% brightness, has an 87% opacity and a 70% gloss rating

TypePaper

Tensile MDTensile CD35 Lbs/in16 Lbs/inTear MDTear CD35 Grams35 Grams

PROPERTIES VALUE

Basis Weight 55

Caliper 2.80 Mil

REGULATORY APPROVAL

RoHS
YesProp65
YesREACH
YesTPCH
YesCPSIA
YesFSC
Yes

ADHESIVE

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

TypeCompositionShearPermanentAcrylic350

Min. Application Temperature Min. Service Temperature Max. Application Temperature

35 F -65 F 200 F

PROPERTIES VALUE

Stainless Steel 5.6 lbs/linear in.

Glass 2,8lbs/linear in.

Polyethylene 2.9

Corrugated 1.50 lbs./in.

Painted Metal

^{*}Please contact your sales representative for details

4.9 lbs/linear in.

Loop Tack 2.70 oz/in²

REGULATORY APPROVAL

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

*Please contact your sales representative for details

Last update: 08/19/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com