

Pressure-sensitive adhesives

Acrylic

FREE-FILM 40#SCK TS523 1.2 MIL POLY

ITEM #9960

ADHESIVE

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

200 F

TypeCompositionShearPermanentAcrylic350

Min. Application Temperature Min. Service Temperature Max. Application Temperature

35 F -65 F

PROPERTIES VALUE

Stainless Steel 5.6 lbs/linear in.

Glass 2,8lbs/linear in.

Polyethylene 2.9

Corrugated 1.50 lbs./in.

Painted Metal 4.9 lbs/linear in.

Loop Tack 2.70 oz/in²

REGULATORY APPROVAL

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

LINER

A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.

Туре
5517342

Tensile MD
30 Lbs/ln
20 Lbs/ln
Tear MD
Tear CD
32 Grams
34 Grams

DESCRIPTION	VALUE

^{*}Please contact your sales representative for details

Basis Weight 40.5 Lbs/Rm

Caliper 2.5 Mil

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

Direct Food

No

LINER

A 1.5 mil polyester liner which has been silicone coated one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end usage, making it an outstanding liner for high speed, automatic applications.

Type 619827

Tensile MD Tensile CD

32000

 Tear MD
 Tear CD

 0
 0

DESCRIPTION VALUE

Caliper 1.5

REGULATORY APPROVAL

RoHS
Yes
Yes
Yes

TPCH
Yes
Yes
Yes

REACH
Yes

UL
No

Direct Food

No

Last update: 05/01/2024

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
800-358-4448
orders.us@beontag.com

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details