



ITEM #F205000J0N000

DESCRIPTION

Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998

FACESTOCK

Scandtherm NTC is a white, woodfree paper, with black imaging thermosensitive coating designed for short term use in relatively clean and dry environments, where there are no requirements for surface protection against contaminants or scuffing. It can be printed with all commonly used technologies for roll converting, including water and uv-based flexo, uv letterpress etc., if inks and varnishes designed for direct thermal paper is used. We recommend customers to assess both pre-print and thermal print characteristics under end-use conditions before proceeding to long runs.

Type
Paper

PROPERTIES	VALUE
Basis Weight	46 lbs/rm
Caliper	3.0 Mil

REGULATORY APPROVAL

RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	UL
Yes	Yes	No
FSC		
Yes		

*Please contact your sales representative for details

ADHESIVE

General purpose, strong permanent adhesive with good chill characteristics. ScandStick Permanent 50N has excellent initial tack with high bond strength at elevated, room and chilled temperatures, as well as in moist conditions. It has been formulated to adhere to a wide variety of substrates, including corrugated cardboard, low surface energy materials like polyethylene and non-polar surfaces. SSP 50N provides enhanced conversion characteristics, allowing die-cutting at higher speeds and is designed for both paper and synthetic face materials. Limitation: Not suitable for labelling plasticized

Type	Composition
Perm	Hotmelt Ru

PROPERTIES	VALUE
------------	-------

Glass	0lbs/linear in.	
Polyethylene	0	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No	Indirect Food Yes	FDA 21 CFR 175.105, BfR XIV No
*Please contact your sales representative for details		

LINER		
HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.		
DESCRIPTION	METHOD	VALUE
Basis Weight	ISO 536	55 ± 3g/m²
Caliper	ISO 534	49 ± 3µ
Transparency	ISO 2469	50%
*Please contact your sales representative for details		

FINAL PRODUCT		
DESCRIPTION	METHOD	VALUE
Typical Caliper	ISO 534	132 ± 10%
Format Roll		
Material Shelf Life 12 months stored at 20°C/50% RH		
*Please contact your sales representative for details		

Last update: 05/01/2024

ADDRESS:
Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50
orders.scandstick@beontag.com